

## **Glossary of Terms**

The following common engineering terms apply to the construction process of the new St. Croix Crossing bridge deck.

**Abutment** – A substructure element that supports each end of a bridge.

**Approach Spans** – The spans connecting the abutment with the main river bridge spans.

**Cable** – Part of a suspension or extradosed bridge extending from an anchorage in the towers and down to the deck anchorage.

Cast-In-Place – Concrete poured within a form at final location to create a final structure.

**Casting Yard** – Location where crews make the pre-cast segments. The St. Croix Crossing project has two—on-site near the Hwy 36/Hwy 95 interchange and at Grey Cloud Island in Cottage Grove.

**Deck** – The roadway portion of a bridge that directly supports vehicle and pedestrian traffic.

**Duct** – Hollow plastic tubing placed inside a form before the concrete pour to leave space for installing the post-tensioned steel strands.

**Footing** – The lower portion of a substructure that distributes the load either to the earth or the supporting piling.

**Form/Casting Bed** – Location where crews pour concrete to create a segment. At the St. Croix Crossing onsite casting yard, these are yellow steel structures.

**Match Casting** – A type of casting method where a new segment's fresh concrete is cast against the hardened concrete of a previously produced segment.

**Pier** – A vertical substructure that supports the spans of the superstructure, including the bridge deck.

**Post-Tensioning** – A method to reinforcing (strengthening) concrete with high-strength steel strands or bars, typically called tendons.

**Pre-Cast** – Built at another location and then transported to the final location to be placed on a structure.

**Rebar Jig** – The location where crews fabricate the rebar cage, which is an element of the segment.

**Reinforcement Bar (Rebar)** – Steel bar used to strengthen and hold the concrete in tension.

**Reinforced Concrete** – Concrete with steel reinforcing bars placed within the structure to supply increased strength and durability.

**Segment** – An element of the bridge made of concrete and steel. Many segments placed next to one another create the bridge driving surface.

**Span** – The distance between piers, towers or abutments.

**Steel** – A material made up of iron and carbon that provides strength.

**Strand** – Pre-stressed steel that is made of seven wires bound/twisted together.

**Substructure** – The parts of the bridge that are below the driving surface. Abutments, pier columns and foundations are part of the substructure.

**Superstructure** – The parts of the bridge that are above the piers columns, including the bridge deck, pier towers and cables.

**Tendon** – Complete assembly of anchorages, pre-stressed steel strand, duct and grout.

Wire – Steel drawn out into the form of a thin flexible thread or rod.